

Drain Guard Drainblok

Ultra Drain Guard

NEW

APPLICATION

- Prevents sediment and other pollutants from entering the drain system

FEATURES & BENEFITS

- Metal frame adjusts and keeps the drain guard in place preventing it from falling into the basin even when the cover grate is removed
- Quick and easy installation, no measuring or cutting of the fabric
- Metal frame can be reused
- Dimensions length x width x height
minimum 406 x 508 x 457mm
maximum 711 x 914 x 457mm
- Performance capacity oil 1.9 litres, sediment 18kgs



| Code | Description | Pack Quantity | Weight kgs |
|------------------------------|------------------------------|---------------|------------|
| ULTRATECH DRAIN GUARD | | | |
| UL-42-445 | Adjustable Frame Drain Guard | 1 | 1.4 |



Drainblok

APPLICATION

- Allows the temporary sealing, blocking of drains, ducts and pipes without the operator having to gain entry into a confined space or even a hazardous area

FEATURES & BENEFITS

- Quick and easy to install
- Inflates in seconds to provide a liquid tight seal in the pipe system
- Resistant to most oils, fuels and non aggressive chemicals
- Easy to clean after use for future deployment
- Reduces the potential pollution risk of hazard fire water runoff
- Supplied as a kit containing low pressure inflator pump unit, 3m extending pole, stopper fitted with 5m airline, manhole keys, operator instructions and storage bag



Code Drain Kit Diameter

DRAINBLOK

| | |
|-----------|-----------------|
| FL-92-110 | Drainblok 100mm |
| FL-92-111 | Drainblok 150mm |
| FL-92-112 | Drainblok 225mm |
| FL-92-113 | Drainblok 300mm |
| FL-92-114 | Drainblok 375mm |
| FL-92-115 | Drainblok 425mm |
| FL-92-116 | Drainblok 600mm |

