

# Absorbent Pads

spilkleen



## MAINTENANCE

Grey in colour, suitable for absorbing most types of industrial spills including both oil and water based liquids including solvents, coolants and mild chemicals. Recommended for internal use.



## OIL & FUEL


White or blue in colour, ideal for where the absorption of oil based liquids such as fuels, lubricants and other hydrocarbon based products is required and for the selective recovery of oil from water. Recommended for external use.




## CHEMICAL

Yellow in colour, designed to absorb aggressive fluids including acids and alkalis. Recommended for internal use.

■ SK-05-110



PERFORATED



MELTBLOWN



■ SK-05-214



■ SK-05-306



A  
PADS



B  
DIMPLED



C  
PERFORATED



D  
BOX



E  
BAG

## APPLICATION

- Suitable for everyday maintenance, repair and general clean up operations

## FEATURES & BENEFITS

- Highly absorbent meltblown absorbent pads
- Bonded and dimpled for additional strength even when contaminated where indicated
- Perforated sheets minimise waste where indicated
- Absorbency rates to suit customers requirements
- Reliable performance
- Dispensing systems available

## HSE RECOMMENDATION ON CHEMICAL SPILLS

- Liquid spills involving hazardous materials should first be contained to prevent spread of the material to other areas. Once the hazardous material has been contained the material should be neutralised to render it safe. Acids and alkalis should be neutralised with appropriate neutralising agents. Please see pages 96-97.

Code	Description	Icon ref	Dimensions cm	Absorbency per pad litres	Quantity per pack
<b>SPIKLEEN MAINTENANCE PADS</b>					
SK-05-110	Heavy Weight	A,B,C,D,E	38 x 50	1.2	100
SK-05-101	Medium Weight	A,B,C,D,E	38 x 50	1	100
SK-05-102	Medium Weight 25	A,B,C,D,E	38 x 50	1	25
SK-05-107-B	Medium Weight	A,B,C,E	35 x 40	0.4	100
SK-05-103	Lightweight	A,B,C,D,E	38 x 50	0.5	200
SK-05-104	Lightweight 100	A,B,C,D,E	38 x 50	0.5	100
<b>SPIKLEEN OIL &amp; FUEL PADS</b>					
SK-05-214	Heavy Weight	A,B,D,E	38 x 50	1.2	100
SK-05-201	Medium Weight	A,D,E	38 x 50	1	100
SK-05-202	Medium Weight 25	A,D,E	38 x 50	1	25
SK-05-209-B	Medium Weight	A,B,C,E	80 x 97	2.4	50
SK-05-203	Lightweight	A,D,E	38 x 50	0.5	200
SK-05-204	Lightweight 100	A,D,E	38 x 50	0.5	100
<b>SPIKLEEN CHEMICAL PADS</b>					
SK-05-306	Heavy Weight	A,B,D,E	38 x 50	1.2	100
SK-05-301	Medium Weight	A,B,C,D,E	38 x 50	1	100
SK-05-302	Lightweight	A,B,C,D,E	38 x 50	0.5	200